

CLAIMS

What is claimed is:

5 1. A pour spout to assist in pouring a liquid from a container including a body having a top opening circumscribed by a rim channel for holding a lid covering said top opening, an inner rim inward of said rim channel, and an outer rim outward of said rim channel, said pour spout comprising:

10 a channel cover for covering said rim channel after a lid covering said top opening is removed from said rim channel, thereby to prevent liquid from dripping into said rim channel after said liquid is removed from said container,

15 a locking flange extending downward of said channel cover, said locking flange being adapted to extend downwardly adjacent said inner rim interiorly thereof,

an outer flange extending downwardly of said channel cover, said outer flange being adapted to extend exteriorly of said outer rim, and

20 a liquid control trough extending upwardly of said channel cover.

2. The pour spout of claim 1, comprising a flexible and resilient plastic material.

25 3. The pour spout of claim 2, wherein said flexible and resilient plastic material comprises polypropylene.

30 4. The pour spout of claim 1, wherein said top opening comprises an annular opening and said channel cover circumscribes said annular opening.

5. The pour spout of claim 1, wherein said outer flange is tapered to a reduced thickness at a free end spaced from said channel cover.
6. The pour spout of claim 1, wherein said locking flange comprises a curved inner rim lock for snapping into engagement with said inner rim.
7. The pour spout of claim 1, wherein said outer flange further comprises an upper flange extending upwardly of said channel cover.
8. The pour spout of claim 7, wherein said upper flange is tapered to a reduced thickness at a free end spaced from said channel cover.
9. The pour spout of claim 1, wherein said liquid control trough comprises a convex exterior surface.
10. The pour spout of claim 9, wherein said pour spout further comprises a drip lip extending exteriorly thereof, said drip lip preventing liquid poured from said container from being transferred onto said convex exterior surface.
11. The pour spout of claim 9, wherein said convex exterior surface displays graphic matter.
12. The pour spout of claim 1 wherein, when said pour spout is inverted over said top opening, said upper flange and said liquid control trough extend downwardly of said outer rim adjacent said container body.
13. The pour spout of claim 1, wherein when said pour spout is inverted over said top opening, said outer flange extends upwardly of said outer rim, thereby enabling a second container to be stacked above said container.

14. The pour spout of claim 1, wherein said pour spout further comprises a stacking spacer adjacent said outer flange and having increased thickness, said stacking spacer evenly distributing weight of a second container stacked over said container.
- 5
15. The pour spout of claim 1, further comprising a pull tab comprising a web extending inward of said channel cover, opposite said liquid control trough.
- 10
16. The pour spout of claim 15, further comprising a curved brush wipe extending inwardly of said channel cover, said brush wipe being located at a position along said channel cover not occupied by said pour trough or said pull tab.
- 15
17. A carrier for a plurality of cylindrical carriers, said carrier comprising a plurality of pour spouts in accordance with claim 1, each said pour spouts being attached to at least one adjacent pour spout by a connector integrally formed therewith.
- 20
18. A carrier in accordance with claim 17, wherein each said connector is sufficiently thin to facilitate separation of said pour spouts via a knife, scissors, or tearing.
- 25
19. A carrier in accordance with claim 17, further comprising a stir paddle integrally formed with said pour spouts.
- 30
20. A carrier in accordance with claim 19, wherein said pour spout includes a shaft and a plurality of blades extending radially outwardly of said shaft, said shaft being suitable for connection with an electric drill in order to mix paint or other liquid.